

**WHAT IS CLAIMED IS:**

1. In a multi-user FWA (fixed wireless access) communication  
2 system in which a plurality of subscriber stations are operable to  
3 communicate by way of radio links with network infrastructure to  
4 which a correspondent node is coupled, an improvement of apparatus  
5 for a selected subscriber station of the plurality of subscriber  
6 stations at which a call of selected call-type is selectively  
7 originated, said apparatus comprising:

a call establishment message generator coupled to receive an indication of initiation at the selected subscriber station of origination of the call, said call establishment message generator for generating a call establishment message for communication to the network infrastructure to initiate call set-up procedures precursing a request to establish the call between the selected subscriber station and the correspondent node;

15 a response detector coupled to receive an indication of a  
16 network-infrastructure generated response to the call establishment  
17 message generated by said call establishment message generator,  
18 said response detector for detecting whether the response to the  
19 call establishment message indicates communication resources to be  
20 available to establish the call; and  
21 a call set-up emulator coupled to said response detector, said

22 call set-up emulator operable to emulate at the selected subscriber  
23 station normal call set-up operations thereat at least for a  
24 selected period responsive to detection by said response detector  
25 of unavailability of the communication resources to establish the  
26 priority call.

1 2. The apparatus of claim 1 wherein said call set-up emulator  
2 comprises a dial-tone generator, said dial-tone generator for  
3 generating an audio dial-tone at the selected subscriber station  
4 responsive to detection by said response detector of the  
5 unavailability of the communication resources.

6 3. The apparatus of claim 2 wherein said subscriber station  
7 comprises a telephonic station having an actuation keypad  
8 actuatable by a user to enter dialing digits associated with the  
9 correspondent node and wherein generation of the audio dial-tone by  
10 said dial-tone generator is terminated upon commencement of entry  
11 of the dialing digits.

1       4. The apparatus of claim 3 further comprising a dialing-  
2 digit signal generator coupled to receive indications of entry of  
3 the dialing digits at the actuation keypad said dialing-digit  
4 signal generator for generating a dialing-digit indication signal  
5 for communication to the network infrastructure pursuant to the  
6 request to establish the call between the subscriber station and  
7 the correspondent node.

*Subb3*  
8       5. The apparatus of claim 1 wherein the correspondent node  
9 comprises an assistance center having a dialing code formed of  
10 dialing digits associated with the assistance center, wherein the  
11 call of the selected call-type comprises a priority call, and  
12 wherein the dialing-digit signal generated by said dialing-digit  
13 signal generator is of values corresponding to the dialing code  
14 associated with the assistance center when the user actuates the  
15 actuation keypad to cause entry of the dialing digits forming the  
16 dialing code associated with the assistance center.

1       6. The apparatus of claim 1 wherein the assistance center  
2       comprises an emergency dispatch center having a pseudo-universal  
3       dialing code associated therewith, wherein the priority call  
4       comprises an emergency call, and wherein the dialing-digit signal  
5       generated by said dialing-digit signal generator is of values  
6       corresponding to the pseudo-universal dialing code associated with  
7       the emergency dispatch center when the user actuates the actuation  
8       keypad to cause entry of the dialing digits forming the pseudo-  
9       universal dialing code.

1       7. In the multi-user FWA communication system of claim 1, a  
2       further improvement of apparatus for the network infrastructure,  
3       said apparatus comprising;

4               a call establishment message detector coupled to receive  
5       indications of receipt at the network infrastructure of the call  
6       establishment message; and

7               a response generator coupled to said call establishment  
8       message detector, said response generator for generating the  
9       response to the call establishment message.

1       8. The apparatus of claim 7 further comprising a  
2 communication resource availability determiner operable responsive  
3 to detection of the call establishment message by said call  
4 establishment message detector, said communication resource  
5 availability determiner for determining whether communication  
6 resources are available to establish the call.

1       9. The apparatus of claim 8 wherein the network  
2 infrastructure is coupled to the correspondent node by way of a  
3 network backbone, and wherein said communication resource  
4 availability determiner determines both whether communication  
5 resources are available upon the network backbone to establish the  
6 call and whether communication resources are available upon the  
radio links to establish the call.

1       10. The apparatus of claim 8 wherein the subscriber station  
2 further sends a dialing digit indication signal to the network  
3 infrastructure and wherein said apparatus for the network  
4 infrastructure further comprises a dialing digit indication  
5 detector coupled to receive indications of receipt at the network  
6 infrastructure of the dialing digit indication signal.

1       11. The apparatus for the network infrastructure of claim 10  
2 further comprising a resource reallocator coupled to said dialing  
3 digit indication detector and to said resource availability  
4 determiner, said resource reallocator selectively operable to  
5 reallocate communication resources in the multi-user FWA  
6 communication system responsive to selected values contained in the  
7 dialing digit indication signal detected by said dialing digit  
8 indication detector.

*Sub B3*  
1       12. The apparatus of claim 11 wherein the correspondent node  
2 comprises an emergency dispatch center having a pseudo-universal  
3 dialing code associated therewith, wherein the dialing digit  
4 indication signal to which said dialing digit indication detector  
5 is coupled to receive indications thereof is of values  
6 corresponding to the pseudo-universal dialing code and wherein said  
7 resource reallocator reallocates the communication resources to  
8 provide communication resources to establish a call between the  
9 subscriber station and the emergency dispatch center.

1       13. The apparatus of claim 12 wherein the communication  
2 resources of the FWA communication system are utilized pursuant to  
3 a plurality of communication resources with a plurality of  
4 subscriber stations and wherein reallocation made by said resource  
5 reallocator include termination of selected communication  
6 resources, thereby to reallocate resources to establish the call  
7 between the subscriber station and the emergency dispatch center.

14. The apparatus of claim 13 wherein the communication sessions have priority levels associated therewith and wherein selection of termination selected communication sessions is made responsive to the priority levels associated with the communication sessions.